logitech®



LOGITECH RALLY BAR

Rally Bar delivers a powerful all-in-one video conferencing experience, featuring brilliant optics, automated PTZ, and high performance audio for midsize meeting rooms. With Rally Bar, video meetings can be just as natural and productive as face-to-face collaboration.

ALL-IN-ONE VIDEO BAR FOR MEDIUM TO LARGE ROOMS

Logitech Rally Bar sets a new standard for video meetings in midsize rooms, with expansion options for larger groups and settings.

It's remarkably simple to use, manage, and deploy at scale, delivering cinema-quality video and audio in a sleek, all-in-one form factor. Plug and play Rally Bar with any PC or Mac, or leverage the built-in compute to run video conferencing applications directly on the device.

Rally Bar features a multi-element lens assembly, powerful low distortion speakers, and an advanced mic system to create meeting experiences that sound as good as they look. A dedicated Al camera amplifies RightSight auto-framing and delivers insights about room usage directly to the Logitech Sync dashboard. Upgrade your video collaboration with Rally Bar.



SIMPLE TO SET UP

USB Plug and Play

Easily connects to virtually any PC or Mac[®], with no additional software required

Appliance Mode

Built-in compute allows you to run supported video conferencing applications such as Zoom directly on the device

All-in-One Design

Sleek, minimal footprint expedites setup and reduces clutter

Streamlined, Flexible Installs

Confidently deploy at scale with smart cable management and multiple mounting options



SIMPLE TO USE

RightSense Technologies

RightSight

Speaker View frames the active speaker while displaying a secondary view of the room to show participant interactions. Group View detects meeting participants automatically adjusts the lens and zoom so no one is left out of the picture.

RightLight

Intelligently adjusts video settings in all light conditions so everyone always looks their best

RightSound

Al-driven voice leveling and unwanted noise suppression deliver outstanding clarity

One-Touch Join

Optionally deploy with Tap to quickly and easily initiate meetings across Zoom, Microsoft Teams, and other cloud services



SIMPLE TO MANAGE

Logitech Sync

Single platform to monitor room health and keep devices up to date, plus insights on room occupancy

Deploy Updates at Scale

Easily propagate upgrades and bug fixes to Rally Bar and your other supported Logitech devices

Forward-Looking Architecture

Sync API is a robust foundation for new insights and integrations

Partner Dashboard Support

Fully integrated with partner solutions like Microsoft Teams, Zoom, and others for a simplified device management experience



AUDIO

Room-filling Sound

Large, ultra low distortion speakers with RightSound convey every word with outstanding clarity

Adaptive Beamforming Mic Array

Beamforming mics pick up voices at every seat and focus on the active talker while suppressing ambient noise

Expansion Ready

Add up to three Rally mic pods for even greater coverage in larger settings

VIDEO

Ultra-HD Video

Brilliantly sharp video, outstanding color, and exceptional optical accuracy at resolutions up to 4K

Expansive Room Coverage

Motorized lens covers rooms 130° across by 80° high, with lossless image quality up to 5X optical zoom

Cinema Quality

Logitech RightLight™ technology captures natural-looking skin tones, even in dim or backlit conditions

AI VIEWFINDER

Framed to Perfection

A second built-in camera lens has the ability to detect meeting participants, amplifying RightSight autoframing

See Everyone Clearly

All meeting participants, even late arrivals, are automatically seen and included

Move About Freely

Al Viewfinder uses scene awareness to keep the camera on the action

ACCESSORIES



TV Mount for Video Bars

Securely mount Rally Bar above or below a TV or monitor



Rally Mic Pod Extension Cable

Easily connect mic pods to Rally Bar with up to two 10m extension cables



Wall Mount for Video Bars

Neatly and confidently secure Rally Bar on the wall for minimal footprint



Rally Mic Pod Mount in **Graphite and White**

Hide cables and anchor mics on the table or ceiling for a clean, finished



Rally Mic Pod in Graphite

Expand audio coverage and provide convenient access to mute controls



Logitech Tap Controller

Deploy with Tap for easy onetouch to join



Rally Mic Pod in White

Expand audio coverage and provide convenient access to mute controls



Rally Mic Pod Hub

Customize microphone placement for your conference table configuration

TECH SPECS

CERTIFICATIONS & COMPATIBILITY GENERAL CAMERA Certifications: Microsoft Teams Rooms on Built-in Components: 6 beamforming Resolution: 4K, 1440p, 1080p, 900p, 720p, and Android (for medium sized rooms), Microsoft microphones, PTZ camera, 2 speakers, Al SD at 30fps Teams Rooms on Windows (for medium sized Viewfinder, cable management & retention Pan: Motorized ±25° system, table stand, Logitech CollabOS platform rooms), Zoom Rooms, Tencent Meeting Rooms Tilt: Motorized ±15° and Lark(Feishu) Rooms on Windows. Enclosure: All-in-one enclosure with integrated table stand and patented speaker suspension Zoom: 15X HD zoom (5X optical, 3X digital Appliance Mode: Supports compatible video available with upcoming software update) system to eliminate vibration-induced camera conferencing software in appliance mode (no PC shake and audio interference required): Microsoft Teams Rooms on Android, Diagonal Field of View: 90° Zoom Rooms, RingCentral Rooms, Tencent Device Management: Logitech Sync Horizontal Field of View: 82.1° Meeting Rooms. Displays Supported: 2 Vertical Field of View: 52.2° USB Mode: Plug and play USB connectivity with virtually any video conferencing application. Display Resolution: Up to 1080p Total Room Coverage: 132.1° Horizontal x 82.2° Vertical For the latest information on certifications and compatibility, visit www.logitech.com/support/ vc-certifications.











RIGHTSENSE™ TECHNOLOGIES DIMENSIONS **SPEAKERS** Drivers: 2x 70mm/2.7 in Height: 164 mm/6.46 in RightLight: Renders natural skin tones for each participant. Width: 910 mm/2.99 ft Output: 90dB SPL @1W, 99dB SPL @8.0W, both +/-2dB at ½ meter RightSight: Primary PTZ camera zooms in on the Depth: 130.5 mm/5.14 in active speaker while the AI Viewfinder captures a Sensitivity: 90+/-3dB SPL at 1W, ½ meter Lens Depth: 28.8 mm/1.13 in view of everyone in the room. THD: 1kHz < 2% Weight: 7.08 kg/15.6 lbs RightSound: Distinguishes speech from other Speaker Sampling Rate: 48 kHz sounds to auto-level voices while suppressing background noise and echo.



MICROPHONES		INTERFACES		POWER & CABLES
Frequency Response: 90Hz – 16kHz Sensitivity: >-36dBFS +/-1dB @ 1Pa Microphone Data Rate Output: 48 kHz Pickup Range: 23 ft (7 m) Beamforming Elements: Six omnidirectional digital MEMS microphones forming five adaptive acoustic broadside beams Audio Processing: AEC (Acoustic Echo Cancellation), VAD (Voice Activity Detector) Noise Suppression: Al filter Add-on Mics: Supports up to 4 additional Rally Mic Pods for larger conference rooms		HDMI Out: 2 (up to 1080) HDMI In: 1 USB 3.0: 3x Type A, 1x Typ Network: 10/100/1G Ethe WiFi: 802.11a/b/g/n/ac (External Mic Input: Yes (p optional Rally Mic Pod, Ro Rally Mic Pod Extension C Remote Control: Bluetoo	one C Prinet MIMO) Proprietary input supports ally Mic Pod Hub, and Cable)	Power Supply: Auto-sensing Operating Voltage/Power: 100-240V, 19V, 4.74A Power Supply Dimensions: 127mm x 51mm x 30mm DC Cable: 1.5m/4.9 ft AC Cable: 1m/3.28 ft HDMI 1.4 Cable: 2m/6.5 ft USB A to USB C 3.0 Cable: 2.2m/7.2 ft
ENVIRONMENTAL				
ENVIROI	NMENTAL	SECU	JRITY	WARRANTY
Operating Temperature: Storage Temperature: -4 Humidity: 10 to 95% BTU/hr: 57 idle, 64 in me	e: 0 to 40 °C 40 to 70 °C	Full Disk Encryption: AES- Data Encryption: Symme Device Identity: Protected Device Access: Authentic Key Protection: Arm Trust	:128 ttric Keys, PKI d by device attestation ated using API	WARRANTY Standard: 2-year limited hardware warranty included Extended: Additional one-year and three-year extended warranties available at the time of hardware purchase. Contact your reseller for availability.
Operating Temperature: Storage Temperature: -4 Humidity: 10 to 95%	e: 0 to 40 °C 40 to 70 °C	Full Disk Encryption: AES- Data Encryption: Symme Device Identity: Protected Device Access: Authentic Key Protection: Arm Trust	:128 ttric Keys, PKI d by device attestation ated using API	Standard: 2-year limited hardware warranty included Extended: Additional one-year and three-year extended warranties available at the time of hardware purchase. Contact your reseller for

logitech[®]

www.logitech.com/RallyBar

Contact your reseller or contact us at www.logitech.com/vcsales

Logitech Americas

7700 Gateway Blvd. Newark, CA 94560 USA

Logitech Europe S.A.

EPFL - Quartier de l'Innovation Daniel Borel Innovation Center CH - 1015 Lausanne

Logitech Asia Pacific Ltd. Tel: 852-2821-5900 Fax: 852-2520-2230

© 2022 Logitech. Logitech, the Logitech logo and other Logitech marks are owned by Logitech and may be registered. All other trademarks are the properties of their respective owners. Logitech assumes no responsibility for any errors that may appear in this publication. Product, pricing and feature information contained herein is subject to change without notice.

Published November 2022